string odbc_cursor(integer result)

Use odbc_cursor to fetch the name of a cursor for a result set.

```
<?
        // connect to database
        $Connection = odbc_connect("store", "guest", "guest");

        // execute query
        $Query = "SELECT name, price ";
        $Query .= "FROM catalog ";
        $Result = odbc_do($Connection, $Query);

        print("Cursor: " . odbc_cursor($Result) . "<BR>\n");

        while(odbc_fetch_row($Result))
        {
              $name = odbc_result($Result, 1);
              $price = odbc_result($Result, 2);

              print("$name: $price<BR>\n");
        }

        odbc_close($Connection);
?>
```

integer odbc_do(integer connection, string query)

Use odbc_do to execute a query on a connection. A result identifier is returned, and is used in many of the other functions for fetching result data.

integer odbc_exec(integer connection, string query)

The odbc_exec function is an alias for odbc_do.

integer odbc_execute(integer result, array parameters)

The odbc_execute function executes a prepared statement. The result argument is an identifier returned by odbc_prepare. The parameters argument is an array that must be passed by reference and will be set with the value of the result columns. See odbc_prepare for an example of use. integer odbc_fetch_into(integer result, array fields) integer odbc_fetch_into(integer result, integer row, array fields) The odbc_fetch_into function gets the specified row for the specified result set and puts the columns into the fields array. The fields argument must be passed by reference. The number of columns in the result set is returned. The row argument may be omitted, in which case the next row in the set is returned.