gunzip -c php-5.x.tar.gz

tar -xvf php-5.x.tar

cd php-5.x

- Configure and Build your PHP, assuming you are using MySQL database.

./configure --with-apxs=/usr/sbin/apxs \

--with-mysql=/usr/bin/mysql

make

make install

- Install the php.ini file. Edit this file to get configuration directives –

cd ../../php-5.x

cp php.ini-dist /usr/local/lib/php.ini

- Tell your Apache server where you want to serve files from, and what extension(s) you want to identify PHP files A .php is the standard, but you can use .html, .phtml, or whatever you want.
  - Go to your HTTP configuration files (/usr/local/apache/conf or whatever your path is)
  - Open httpd.conf with a text editor.
  - Search for the word DocumentRoot (which should appear twice), and change both paths to the directory you want to serve files out of (in our case, /home/httpd). We recommend a home directory rather than the default /usr/local/apache/htdocs because it is more secure, but it doesn.t have to be in a home directory. You will keep all your PHP files in this directory.
- Add at least one PHP extension directive, as shown in the first line of code that follows. In the second line, we.ve also added a second handler to have all HTML files parsed as PHP.

AddType application/x-httpd-php .php

AddType application/x-httpd-php .html

- Restart your server. Every time you change your HTTP configuration or php. ini files, you must stop and start your server again.

cd ../bin

./apachectl start