The optional type argument specifies a data type and is necessary if you wish to bind to an abstract data type. Use one of the following constants to set the data type: OCI_B_BLOB, OCI_B_CFILE, OCI_B_CLOB, OCI_B_FILE, OCI_B_ROWID. Make sure you use ocinewdescriptor before binding to an abstract data type. You also need to use -1 for the length argument.

```
<?
        //set-up data to insert
        $NewEmployee = array(
              array(8001, 'Smith', 'Clerk'),
              array(8002, 'Jones', 'Analyst'),
              array(8003, 'Atkinson', 'President')
              );

        //connect to database
        $Connection = ocilogon("scott", "tiger");

//assemble query
$Query = "INSERT INTO emp (EMPNO, ENAME, JOB, HIREDATE) ";
$Query .= "VALUES (:empno, :ename, :job, SYSDATE ) ";
$Query .= "RETURNING ROWID INTO :rowid ";

//parse query
$Statement = ociparse($Connection, $Query);

//create descriptor the abstract data type
$RowID = ocinewdescriptor($Connection, OCI_D_ROWID);

//bind input and output variables
ocibindbyname($Statement, ":empno", &$EmployeeNumber, 32);
ocibindbyname($Statement, ":ename", &$EmployeeName, 32);
ocibindbyname($Statement, ":job", &$Job, 32);
ocibindbyname($Statement, ":rowid", &$RowID, -1, OCI_B_ROWID);

          //loop over each new employee
          while(list($key, $EmployeeInfo) = each($NewEmployee))
          {
                list($EmployeeNumber, $EmployeeName, $Job) =
 $EmployeeInfo;

                //execute query, do not automatically commit
                ociexecute($Statement, OCI_DEFAULT);

                print("$EmployeeNumber has ROWID $RowID<BR>\n");
          }

          //free the statement
          ocifreestatement($Statement);
```