array ocierror(integer identifier)

If an error has occurred, the ocierror function returns an associative array that describes it. If no error has occurred, FALSE is returned. The identifier argument may be either a statement identifier or a connection identifier. The returned array will have two elements, code and message. You may also call ocierror with no argument to get information about a failed login.

boolean ociexecute(integer statement, integer mode)

Use ociexecute to execute a statement. The mode argument is optional. It controls whether the statement will be committed after execution. By default, OCI_COMMIT_ON_EXECUTE is used. If you do not wish to commit the transaction immediately, use OCI_DEFAULT.

boolean ocifetch(integer statement)

The ocifetch function prepares the next row of data to be read with ociresult. When no rows remain, FALSE is returned.

```
<?
        //connect to database
        $Connection = ocilogon("scott", "tiger");

        //assemble query
        $Query = "SELECT * ";
        $Query .= "FROM emp ";

        //parse query
        $Statement = ociparse($Connection, $Query);

        //execute query
        ociexecute($Statement);

       //check that the query executed sucessfully
       if($Error = ocierror($Statement))
       {
             print($Error["code"] . ": " . $Error["message"]
<BR>\n");
             exit;
       }

       //start HTML table
       print("<TABLE>\n");

   //build headers from column information
   print("<TR>\n");
   for($i=1; $i = ocinumcols($Statement); $i++)
   {
```