bits that make up the integer values. Since these types of operators converts integer numbers to binary numbers and performs logical operations then finally display them in integer numbers, thus the name bitwise operators. AND(&), OR(|), XOR(^), NOT(~), Shift left(<<) and Shift right(>>) are the most commonly used bitwise operators.

Here is an example that shows the uses of PHP bitwise AND(&) operator which displays the output of bitwise AND operation of two variables $a and $b.

```
<?php

$a=66;

$b=88;

$c=$a&$b;

echo "Bitwise AND on a and b is $c";

?>
```

Output:

Bitwise AND on a and b is 64

2.2.5 Comparison Operators

Since, logical operator provides the way to make decisions, comparison operator provides a method to direct program flow. Comparison operator compares the two or more values of the variables. Some of the most commonly used comparison operators are less than (<), greater than (>), less than or equal to (<=), greater than or equal to (>=) and ternary operator (? :).

Here is an example showing how comparison operators are used in PHP.

- Equality (==) returns true if both operands are equal, otherwise returns false.
- Identity(===) return true if both operands have the same data type and equal, otherwise return false.
- Inequality(!= or <>) returns true if both operands are not equal, otherwise return false.
- Not identical (!===) returns true if both operands are not equal or not have the same data type, otherwise returns false.