Parsing is used in all **high-level programming languages**. Languages like C++ and Java are parsed by their respective compilers before being transformed into executable machine code. Scripting languages, like PHP and Perl, are parsed by a .web server, allowing the correct HTML to be sent to a browser

4.2.1 Variable parsing

When a string is specified in double quotes or with heredoc, variables are parsed within it.

There are two types of syntax: a simple one and a complex one. The simple syntax is the most common and convenient. It provides a way to embed a variable, an array value, or an object property in a string with a minimum of effort.

The complex syntax can be recognized by the curly braces surrounding the expression.

If a dollar sign ($) is encountered, the parser will greedily take as many tokens as possible to form a valid variable name. Enclose the variable name in curly braces to explicitly specify the end of the name.

```
<?php
$juice = “apple”;


echo “He drank some $juice juice.”.PHP_EOL;
// Invalid. “s” is a valid character for a variable name, but the variable is $juice.
echo “He drank some juice made of $juices.”;
// Valid. Explicitly specify the end of the variable name by enclosing it in braces:
echo “He drank some juice made of ${juice}s.”;
?>
```

The above example will output:

He drank some apple juice.

He drank some juice made of .

He drank some juice made of apples.

Similarly, an array index or an object property can be parsed. With array indices, the closing square bracket (*]*) marks

Keyword

High-level programming language is a programming language with strong abstraction from the details of the computer. In contrast to low-level programming languages, it may use natural language elements, be easier to use, or may automate (or even hide entirely) significant areas of computing systems (e.g. memory management), making the process of developing a program simpler and more understandable than when using a lower-level language.