From the same Car class, we created three individual objects with the name of: Mercedes, Bmw, and Audi.

Although all of the objects were created from the same class and thus have the class's methods and properties, they are still different. This is not only, because they have different names, but also because they may have different values assigned to their properties. For example, in the image above, they differ by the color property - the Mercedes is green while the Bmw is blue and the Audi is orange.

6.1.2 Defining Classes and Objects

Before creating any new object, you need a class or blueprint of the object. It is pretty easy to define a new class in PHP. To define a new class in PHP you use the class keyword as the following example:

```php
<?php
class BankAccount{

}
```

We've defined a new empty class named BankAccount. From the BankAccount class, we can create new bank account object using the new keyword as follows:

```php
<?php
class BankAccount{

}

// create a new bank account object
$account = new BankAccount();

var_dump($account);
```

Notice that we use var_dump() function to see the content of the bank account.

6.1.3 Properties

In object-oriented terminology, characteristics of an object are called *properties*. For example, the bank account has account number and total balance. So let's add those properties to the BankAccountclass:

```php
<?php
class BankAccount{
 private $accountNumber;
 private $totalBalance;
}
```

You see that we used the private keyword in front of the properties. This is called property visibility. Each property can have one of three visibility levels, known as private, protected and public.