```
// create a new bank account object
$account = new BankAccount();

$account->setAccountNumber('1243845355');
echo sprintf("Bank account # %s<br/>",$account->getAccountNumber());

echo sprintf("Deposit $2000 to the bank account.<br/>");
$account->deposit(2000);
echo sprintf("Total balance %0.2f<br/>", $account->getBalance());

echo sprintf("Withdraw $100 from the bank account.<br/>");
$account->withdraw(100);
echo sprintf("Total balance %0.2f<br/>", $account->getBalance());

echo sprintf("Withdraw $2000 from the bank account.<br/>");
$account->withdraw(2000);
```

you have learned the basic PHP object-oriented programming (OOP). You also learned the two important building blocks of PHP OOP, objects, and classes.

6.2 CREATING AN OBJECT

It is much easier to create objects and use them than it is to define object classes, so before we discuss how to define classes, let's look at creating objects. To create an object of a given class, use the new keyword:

*$object = **new** Class;*

Assuming that a Person class has been defined, here's how to create a Person object:

```
$rasmus = new Person;
```

Do not quote the class name, or you'll get a compilation error:

```
$rasmus = new 'Person';                    // does not work
```

Some classes permit you to pass arguments to the new call. The class's documentation should say whether it accepts arguments. If it does, you'll create objects like this:

```
;(object = new Person('Fred', 35$
```

The class name does not have to be hardcoded into your program. You can supply :the class name through a variable