boolean dba_optimize(integer link)

Use dba_optimize to optimize a database, which usually consists of eliminating gaps between records created by deletes. This function returns TRUE on success. Some underlying engines do not support optimizations, in which case this function will have no effect

```
<?
  // open database in write mode
  $db = dba_popen('inventory', 'w', 'gdbm');

  if($db)
  {
    //optimize database
    dba_optimize($db);

    // close database
    dba_close($db);
  }
  else
  {
    print('Database does not exist');
  }
?>
```

integer dba_popen(string filename, string mode, string type, ...)

The dba_popen function behaves identically to dba_open with one difference: Links are not closed. They remain with the process until the process ends. When you call dba_popen, it first tries to find an existing link. Failing that, it will create a new link. You never call dba_close on a link returned by dba_popen.

Since the links are pooled on per-process basis, this functionality offers no benefit when using PHP as a stand-alone executable. When used as an Apache module, there may be some small performance benefit due to the unique way Apache uses child processes.

boolean dba_replace(string key, string value, integer link)

Use dba_replace to update the value of an existing record. As with the other DBA functions, a valid link as returned by dba_open or dba_popen should be used for the link argument.

boolean dba_sync(integer link)

The dba_sync function will synchronize the view of the database in memory and its image on the disk. As you insert records, they may be cached in memory by the