integer ifx_affected_rows(integer result)

The ifx_affected_rows function returns the number of rows selected, inserted, updated, or deleted, depending on the query. If the query was a select, the number is only an estimate. You can use this function on a result identifier returned by ifx_prepare in order to avoid executing queries that will return large result sets.

boolean ifx_blobinfile_mode(integer mode)

Use ifx_blobinfile function to control how to work with blobs. If mode is 0, blobs are saved in memory. If mode is 1, blobs are saved to disk.

boolean ifx_byteasvarchar(integer mode)

Use ifx_byteasvarchar to control how byte blobs are returned in queries. If mode is 0, blob IDs are returned. If mode is 1, blob contents are returned.

boolean ifx_close(integer link)

The ifx_close function closes a database connection created by ifx_connect. If the optional link argument is left out, the last-opened connection is closed.

integer ifx_connect(string database, string user, string password)

The ifx_connect function returns a connection to an Informix database. All of the arguments are optional and will draw their values from the php.ini file if necessary. If a connection cannot be established, FALSE is returned. If you attempt to connect again after successfully connecting, the original connection identifier is returned. The connection will be closed automatically when the script ends, but you can close it manually with ifx_close. The ifx_pconnect function creates a persistent connection.

integer ifx_copy_blob(integer blob)

The ifx_copy_blob function makes a copy of an existing blob and returns the identifier to the new blob.

integer ifx_create_blob(integer type, integer mode, string data)

The ifx_create_blob function creates a blob in the database. The type argument can be 1 for text or 0 for byte. The mode argument is set to 0 if the data argument contains data to place in the blob. The mode is set to 1 if the data argument is a path to a file.