```
<?
  //connect to database
  if(!($dbLink = ifx_pconnect("mydb@ol_srv1", "
leon", "secret"))
  {
    print("Unable to connect!<BR>\n");
    exit();
  }

  //create blob and add to array
  $blob[] = ifx_create_blob(0, 0, "This is a message");

  //insert message
  $Query = "INSERT INTO message " .
    "VALUES (3,'My Title', ?)";

  if(!($result = ifx_query($Query, $dbLink, $blob))
  {
    print("Unable to insert message!<BR>\n");

    //print Informix error message
    print(ifx_error() . "<BR>\n");
    print(ifx_errormsg() . "<BR>\n");
  }

  //free result identifier
  ifx_free_result($result);

  //close connection
  ifx_close($dbLink);
?>
```

### *integer ifx_create_char(string data)*

The ifx_create_char function creates a character object. An identifier for the character object is returned.

### *boolean ifx_do(integer result)*

The ifx_do function executes a query prepared with ifx_prepare. The result argument must be as returned by ifx_prepare.

### *string ifx_error()*

Use ifx_error to fetch the error produced by the last query. The first character of the returned string is a flag reporting the type of condition. A space means no error. E is an error. N means no more data is available. W is a warning. A ? signals an unknown error condition. If anything other than a space is returned in the first character, the string will contain extra information, including an error code.