string ifx_get_blob(integer blob)

The ifx_get_blob function returns the contents of a blob.

array ifx_getsqlca(integer result)

The ifx_getsqlca function returns an array of the values in the sqlerrd struct from the underlying Informix API.

integer ifx_htmltbl_result(integer result, string options)

The ifx_htmltbl_result function prints an HTML table containing all the rows in the result set. The optional options argument will be placed inside the table tag.

boolean ifx_nullformat(integer mode)

When mode is 0, ifx_nullformat will cause all null columns to be returned as empty strings. If mode is 1, they are returned as NULL, a four-character string.

integer ifx_num_fields(integer result)

The ifx_num_fields function returns the number of columns in the result set.

integer ifx_num_rows(integer result)

Use ifx_num_rows to get the exact number of rows already fetched for a result set. To get an approximate number of rows in a result set, use ifx_affected_rows.

integer ifx_pconnect(string database, string user, string password)

The ifx_pconnect function is similar to ifx_connect, except that connections are not closed until the Web server process ends. Persistent links remain available for subsequent connection attempts by other scripts.

```
<?
  //connect to database
  if(!($dbLink = ifx_pconnect("mydb@ol_srv1", "leon", "secret"))
  {
    print("Unable to connect!<BR>\n");
    exit();
  }
  //treat blobs as varchars
  ifx_textasvarchar(TRUE);

  //get a record from the message table
  $Query = "SELECT Title, Body FROM message " .
    "WHERE ID = 3 ";
  if(!($result = ifx_query($Query, $dbLink))
  {
    print("Unable to query message table!<BR>\n");
```