```
  }

  //print results in HTML table
  ifx_htmltbl_result($result);

  //free result identifier
  ifx_free_result($dbLink);

  //close connection
  ifx_close($dbLink);
?>
```

integer ifx_prepare(string query, integer link, integer cursor_type, array blob_id)

The ifx_prepare function parses a query but does not execute it. Otherwise it operates identically to ifx_query. To execute the query, use ifx_do.

```
<?
  //connect to database
  if(!($dbLink = ifx_pconnect("mydb@ol_srv1", "leon", "secret"))
  {
    print("Unable to connect!<BR>\n");
    exit();
  }

//get message about PHP
$Query = "SELECT ID, Title FROM message " .
  "WHERE Title like '%PHP%' ";
if(!($result = ifx_prepare($Query, $dbLink, IFX_SCROLL))
{
  print("Unable to query message table!<BR>\n");
}

if(ifx_affectedrows($result)  100)
{
  //execute query
  ifx_do($result);

  //fetch each row, print a link
  while($row = ifx_fetch_row($result, "NEXT"))
  {
    print("A HREF=\"get.php?id={$row["ID"]}\">");
    print("{$row["Title"]}/A><BR>\n");
  }
}
else
{
  print("Too many results to display on one page.<BR>\n");
}
```