```
<?
  $Link = msql_connect("msql.clearink.com");
  msql_select_db("store", $Link);

  $Query = "SELECT * FROM item i, SKU s ";
  $Query .= "WHERE i.SKU = s.ID ";
  $Result = msql_query($Query, $Link);

  // get description of each field
  // starting with the third
  msql_field_seek($Result, 2);


while($Field = msql_fetch_field($Result))
{
   print("Name: " . $Field->name . "<BR>\n");
   print("Table: " . $Field->table . "<BR>\n");
   print("Not Null: " . $Field->not_null ."<BR>\n");
   print("Primary Key: " . $Field->primary_key"<BR>\n");
   print("Unique: " . $Field->unique . "<BR>\n");
   print("Type: " . $Field->type . "<BR>\n<BR>\n");
}

  msql_close($Link);
?>
```

string msql_fieldflags(integer result, integer field)

The msql_fieldflags function returns all the flags turned on for the specified field. These may be primary key, unique, and not null.

```
<?
  $Link = msql_connect("msql.clearink.com");
  msql_select_db("store", $Link);

  $Query = "SELECT * FROM item";
  $Result = msql_query($Query, $Link);
  print("Field 0 flags are " .msql_fieldflags($Result, 0));

  msql_close($Link);
?>
```

integer msql_fieldlen(integer result, integer field)

The msql_fieldlen function returns the length of the specified field.