msql_regcase

This is an alias to sql_regcase.

string msql_result(integer result, integer row, string field)

The msql_result function returns a single field value for the given row. The field argument can be interpreted in two ways. If it is a number, it will be used as a field offset, starting with zero. Otherwise, it will be considered to be a column name.

The msql_result function is relatively slow. Its use should be avoided in favor of faster functions such as msql_fetch_array.

```
<?
  $Link = msql_connect("msql.clearink.com");
  msql_select_db("store", $Link);

  $Query = "SELECT * FROM item i, SKU s ";
  $Query .= "WHERE i.SKU = s.ID ";
  $Result = msql_query($Query, $Link);

  $numRows = msql_num_rows($Result);

  for($index = 0; $index  $numRows; $index++)

 {
   $item_ID = msql_result($Result, $index, "item.ID");
   $item_Name = msql_result($Result, $index, "item.Name");

   print("$item_ID: $item_Name<BR>\n");
 }

 msql_close($Link);
?>
```

boolean msql_select_db(string database, integer link)

Use msql_select_db to select the database against which to make queries. As with most other mSQL functions, the link identifier is not required.

8.7 MYSQL

MySQL is a relational database with a license that allows you to use it cost-free for most noncommercial purposes. It shares many features with mSQL because it was originally conceived as a faster, more flexible replacement. Indeed, MySQL has delivered on these goals. It easily outperforms even commercial databases. Not surprisingly, MySQL is the database of choice for many PHP developers.

As with mSQL, there were MySQL functions in PHP2 that are still supported in PHP3, but their use is discouraged. We have chosen to leave these functions out of the reference. The functions we have left out are mysql, mysql_cre- atedb, mysql_dbname,