boolean mysql_change_user(string user, string password, string database, integer link)

Use mysql_change_user to change the user for a database connection. The database and link arguments are optional. If left out, the current database and the link last opened are used. If the user cannot be changed, the current connection remains open with the original user. This function requires MySQL version 3.23.3 or newer.

```
<?
  //connect to server as freetrade user, no password
  $dbLink = mysql_pconnect("localhost", "freetrade", "");

  //select the 'freetrade' database
  mysql_select_db("freetrade", $dbLink);

  //switch to admin user
  mysql_change_user("admin", "secret", "freetrade", $dbLink);
?>
```

boolean mysql_close(integer link)

Use mysql_close to close the connection to a database. The connect must have been opened with mysql_connect. Use of this function is not strictly necessary, as all nonpersistent links are closed automatically when the script finishes. The link argument is optional, and when it's left out, the connection last opened is closed.

```
<?
  // open connection
  $Link = mysql_connect("localhost", "httpd", "");

  // close connection
  mysql_close($Link);
?>
```

integer mysql_connect(string host, string user, string password)

The mysql_connect function begins a connection to a MySQL database at the specified host. If the database is on a different port, follow the hostname with a colon and a port number. You may alternatively supply a colon and the path to a socket if connecting to localhost. This might be written as localhost:/tmp/sockets/mysql. All the arguments are optional and will default to localhost, the name of the user executing the script, and an empty string, respectively. The user executing the script is typically httpd, the Web server.

Connections are automatically closed when a script finishes execution, though they may be closed earlier with mysql_close. If you attempt to open a connection that is already open, a second connection will not be made. The identifier of the previously open connection will be returned.