FALSE is returned in the event of an error.

```
<?
  //establish connection
  if(!($dbLink = mysql_connect("localhost:3606", "freetrade", "")))
  {
    print("mysql_connect failed!<BR>\n");
  }

  //select database
  if(!(mysql_select_db("freetrade", $dbLink)))
  {
    print("mysql_select_db failed!<BR>\n");
    print(mysql_errno() . ": ");
    print(mysql_error() . "<BR>\n");
  }
```

Remember

Note that you must open a connection with an account that has permission to create databases. If you leave out the link argument, the last-opened connection will be used.

boolean mysql_create_db(string database, integer link)

Use mysql_create_db to create a new database.

```
<?
  // open connection
  $dbLink = mysql_connect("localhost", "admin", "secret");

  //create database
  mysql_create_db("garbage", $dbLink);
?>
```

boolean mysql_data_seek(integer result, integer row)

The mysql_data_seek function moves the internal row pointer of a result set to the specified row. Use this function with mysql_fetch_row to jump to a specific row. The result argument must have been returned from mysql_query or a similar function.

```
<?
  //connect to server as freetrade user, no password
  $dbLink = mysql_pconnect("localhost", "freetrade", "");

  //select the 'freetrade' database
  mysql_select_db("freetrade", $dbLink);

  //get states from tax table
  $Query = "SELECT State " .
    "FROM tax ";
  $dbResult = mysql_query($Query, $dbLink);

  //jump to fifth row
  mysql_data_seek($dbResult, 4);
```