Compare this function to mysql_ fetch_array and mysql_fetch_object. There is not much difference in performance between these three functions.

```
<?
  //connect to server as freetrade user, no password
  $dbLink = mysql_pconnect("localhost", "freetrade", "");

  //select the 'freetrade' database
  mysql_select_db("freetrade", $dbLink);

  //get unique cities from address table
  $Query = "SELECT City, StateProv " .
    "FROM address ";
  $dbResult = mysql_query($Query, $dbLink);


  //get each row
  while($row = mysql_fetch_row($dbResult))
  {
    // print city, state
    print("$row[0], $row[1]<<BR>\n");
  }
?>
```

string mysql_field_flags(integer result, integer field)

Use mysql_field_flags to get a description of the flags on the specified field. The flags are returned in a string and separated by spaces. The flags you can expect are auto_increment, binary, blob, enum, multiple_key, not_null, primary_key, timestamp, unique_key, unsigned, and zerofill. Some of these flags may be available only in the newest versions of MySQL.

integer mysql_field_len(integer result, integer field)

Use mysql_field_len to get the maximum number of characters to expect from a field. The fields are numbered from zero.

string mysql_field_name(integer result, integer field)

Use mysql_field_name to get the name of a column. The field argument is an offset numbered from zero.

boolean mysql_field_seek(integer result, integer field)

The mysql_field_seek function moves the internal field pointer to the specified field. The next call to mysql_fetch_field will get information from this field.