```
<?
        // connect to database
        $Connection = odbc_connect("store", "guest", "gu

        // execute query
        $Query = "SELECT name, price ";
        $Query .= "FROM catalog ";
        $Result = odbc_do($Connection, $Query);

        // free the result set
        odbc_free_result($Result);
```

### *boolean odbc_longreadlen(integer result, integer length)*

Use odbc_longreadlen to set the maximum length for values of any columns of type long. This includes binary columns such as longvarbinary. By default the maximum length is zero, which has the special meaning of causing fetched columns to be echoed to the browser. Any other positive number will cause returned values to be truncated to the specified length.

Note that it is not always apparent that a field is considered to be a long by the ODBC driver.

*A memo column in Microsoft Access is a long. Data appearing in the wrong place are a sign of fetching a long where you did not expect it. One strategy to avoid these problems is to always call longreadlen.*




### *integer odbc_num_fields(integer result)*

Use odbc_num_fields to find the number of fields in the result set.

```
<?
        // connect to database
        $Connection = odbc_connect("store", "guest", "guest");


         // execute query
         $Query = "SELECT name, price ";
         $Query .= "FROM catalog ";
         $Result = odbc_do($Connection, $Query);

         print(odbc_num_fields($Result));

         odbc_close($Connection);
?>
```