```
        {
              $values[0] = $index-2000;
              $values[1] = "$index Calendar";
              $values[2] = 20.00 + (0.50 * ($index-2000));

              odbc_execute($Result, $values);
        }

        odbc_close($Connection);
?>
```

string odbc_result(integer result, string field)

Use odbc_result to get the value of a field for the current row. Fields may be referenced by number or name. If by using numbers, start counting fields with 1. If you specify a field by name, do not include the table name.

This function is affected by the settings controlled by odbc_binmode and odbc_longreadlen. An important fact to keep in mind is that while in most cases the value of the field will be returned, fields that contain long data will be echoed to the browser instead by default. Use odbc_longreadlen to change this behavior.

```
<?
        // connect to database
        $Connection = odbc_connect("store", "guest", "guest");

        // execute query
        $Query = "SELECT name, price ";
        $Query .= "FROM catalog ";


      $Result = odbc_do($Connection, $Query);

      while(odbc_fetch_row($Result))
      {
      $name = odbc_result($Result, 1);
      $price = odbc_result($Result, 2);
            print("$name: $price<BR>\n");
      }

      odbc_close($Connection);
?>
```

integer odbc_result_all(integer result, string format)

The odbc_result_all function will dump all the rows for a result set to the browser. The number of rows is returned. The dumped rows will be formatted in a table. The field names will be printed in a header row with TH tags. The optional format argument will be inserted inside the initial table tag so that you may set table attributes.