```
<?
        // connect to database
        $Connection = odbc_connect("store", "guest", "guest");

        // execute query
        $Query = "SELECT name, price ";
        $Query .= "FROM catalog ";
        $Result = odbc_do($Connection, $Query);

        // dump all results
        odbc_result_all($Result, "BORDER=1");

        odbc_close($Connection);
?>
```

boolean odbc_rollback(integer connection)

Use odbc_rollback to abandon all pending transactions. By default all queries are automatically committed, but this behavior may be modified with odbc_autocommit. Not all databases support transactions.

```
<?
        // connect to database
        $Connection = odbc_connect("store", "guest", "guest");

        // turn off autocommit
        odbc_autocommit($Connection, FALSE);


         // put everything on sale
         $Query = "UPDATE catalog ";
         $Query .= "SET price = price * 0.9 ";
         $Result = odbc_do($Connection, $Query);

         // rollback
         odbc_rollback($Connection);

         odbc_close($Connection);
?>
```

integer odbc_setoption(integer id, integer function, integer option, integer parameter)

The odbc_setoption function changes the configuration of the ODBC driver for an entire connection or a single result set. Its purpose is to allow access to any ODBC setting in order to avoid problems with buggy ODBC drivers. To use this function, you ought to understand ODBC in greater detail than the average user. You will need to know the values of the various options available to you.

The id argument is either a connection identifier or a result set identifier. Since odbc_setoption wraps two C API functions, SQLSetConnectOption and SQLSetStmtOption,