boolean ocilogoff(integer connection)

Use ocilogoff to close a connection.

integer ocilogon(string user, string password, string sid)

The ocilogon function establishes a connection to an Oracle database. The identifier it returns is used to create statements, cursors, and descriptors. The user and password arguments are required. The optional sid argument specifies the server; if it is left out, the ORACLE_SID environment variable will be used.

If you attempt to create a second connection to the same database, you will not really get another connection. This means that commits or rollbacks affect all statements created by your script. If you want a separate connection, use ocinlogon instead.

integer ocinewcursor(integer connection)

Use ocinewcursor to create a cursor. The cursor identifier that is returned is similar to a statement identifier. Use ocifreecursor to free the memory associated with a cursor. You can use a cursor to get the data returned by a stored procedure.

```
<?
        //open connection
        $Connection = ocilogen ("scott", "tiger");

        //create cursor

 $Cursor = ocinewcursor ($Connection);

 //create statement that calls a stored procedure
 $Query = "BEGIN ";
 $Query .= "docalculation;(:price); ";
 $Query .= "END; ";
 $Statement = ociparse ($Connection, $Query);

 //bind placeholder to cursor
 ocibindbyname ($Statement, "price", &$Cursor, -1, OCI_B_CURSOR)

 //execute statement
 ociexecute ($Statement);

 //execute cursor
 ociexecute($Cursor);

 //loop over results in cursor
 while (ocifetchinto ($Cursor, &$Results))
 {
        print("$Results<BR>\n")
 }

 //free memory for cursor
 ocifreecursor ($Cursor);
```