```
//free memory for statement
ocifreestatement ($Statement);

//close connection
ocilogoff ($Connection);
```

string ocinewdescriptor(integer connection, integer type)

The ocinewdescriptor function allocates memory for descriptors and LOB locators. The type defaults to being a file, but you may specify OCI_D_FILE, OCI_D_LOB, or OCI_D_ROWID.

integer ocinlogon(string user, string password, string sid)

The ocinlogon function establishes a unique connection to an Oracle database. The identifier it returns is used to create statements, cursors, and descriptors. The user and password arguments are required. The optional sid argument specifies the server, and if left out, the ORACLE_SID environment variable will be used.

Compare this function to ocilogon and ociplogon.

integer ocinumcols(integer statement)

The ocinumcols function returns the number of columns in a statement.

integer ociparse(integer connection, string query)

The ociparse function creates a statement from a query. It requires a valid connection identifier.

integer ociplogon(string user, string password, string sid)

The ociplogon function establishes a persistent connection to an Oracle database. These connections exist as long as the server process. When you request a persistent connection, you may get a connection that already exists, thus saving the overhead of establishing a connection. The returned identifier is used to create statements, cursors, and descriptors. The user and password arguments are required. The optional sid argument specifies the server, and if left out, the ORACLE_SID environment variable will be used. Compare this function to ocilogon and ocinlogon.