```
;“echo “Third Element: $intArray[2]\n

<?
```

Output:

```
First Element: 10
Second Element: 20
    Third Element: 30
```

Objects: Objects are defined as instances of user defined classes that can hold both values and functions.

Resources: Resources in PHP are not an exact data type. These are basically used to store references to some function call or to external PHP resources. For example, consider a database call. This is an external resource.

Did You Know?

HipHop – developed at Facebook and available as open source, it transforms the PHP scripts into C++ code and then compiles the resulting code, reducing the server load up to 50%. In early 2013, Facebook deprecated it in favor of HHVM due to multiple reasons, including deployment difficulties and lack of support for the whole PHP language, including the create_function() and eval() constructs.

2.2 PHP OPERATORS

An operator takes one or more values, which are known as operands, and performs operation on them such as adding them together. The following are the most common used operators in PHP:

- Arithmetic Operators
- Assignment Operators
- Bitwise Operators
- Comparison Operators
- Increment/Decrement Operators
- Logical Operators
- Concatenating Operators

2.2.1 Arithmetic Operators

The arithmetic operators require numeric values. And non-numeric values are converted automatically to numeric values. The following are the list of arithmetic operators:

- Addition (+) returns the sum of two operands
- Subtraction (-) returns the difference between two operands