- ru_idrss: integral unshared data size
- ru_minflt: page reclaims
- ru_majflt: page faults
- ru_nsignals: signals received
- ru_nvcsw: voluntary context switches
- ru_nivcsw: involuntary context switches
- ru_nswap: swaps
- ru_utime.tv_usec: user time used (microseconds)
- ru_utime.tv_sec: user time used (seconds)
- ru_stime.tv_usec: system time used (microseconds)
- ru_stime.tv_sec: system time used (seconds)

To see how much CPU power the script has consumed, we need to look at the 'user time' and 'system time' values. The seconds and **microseconds** portions are provided separately by default. You can divide the microseconds value by 1 million, and add it to the seconds value, to get the total seconds as a decimal number.

Keyword

Microsecond is an SI unit of time equal to one millionth (0.000001 or 10–6 or 1⁄1,000,000) of a second.

Let's see an example:

```
// sleep for 3 seconds (non-busy)
sleep(3);

$data = getrusage();
echo "User time: ".
    ($data['ru_utime.tv_sec'] +
    $data['ru_utime.tv_usec'] / 1000000);
echo "System time: ".
    ($data['ru_stime.tv_sec'] +
    $data['ru_stime.tv_usec'] / 1000000);

/* prints
User time: 0.011552
System time: 0
*/
```