```
helloWorld();
HELLOWORLD();

function helloWorld()
{
    print "Hello world!" . PHP_EOL;
}

Output:
Hello world!
Hello world!
```

The code above demonstrates a number of things. We create a function called `helloWorld()` using the `function` keyword and add a single statement inside the function braces: a simple `print` to show the program is working. The function is called by using its name followed by parentheses like so: `helloWorld()`. Functions defined in this way are sometimes called "user-land," a name that serves to differentiate them from PHP's many, many built-in functions.

Two important things to note here. Firstly, function names are not case sensitive (unlike variable names). `helloWorld` and `HELLOWORLD` in the context of a function are equivalent. Secondly, it is not necessary to define a function before using it. Before the code executes, the PHP engine has already parsed the text of the program and encountered the function declaration. At runtime the PHP engine already knows about `helloWorld()` and what it does. This is sometimes called "function hoisting," because semantically the function declaration behaves as if it had been placed at the top of the file (it has been hoisted to the top).

There is one caveat with function hoisting: if a function declaration is found inside a conditional statement or a conditionally included file, it cannot be used until PHP encounters it during execution.

```
goodMorning();
helloWorld();

if (true) {
    function helloWorld()
    {
        print "Hello world!" . PHP_EOL;
    }
}
```