```
$obj = new ArrayObject([
    'a car',
    'a guitar',
    'and a nice cold pint',
]);

countAndIterate($obj);
```

```
Output:
Data contains 3 things:
string(5) "a car"
string(8) "a guitar"
string(20) "and a nice cold pint"
```

When the `new ArrayObject` is created, we give it an array. Don't worry that it looks a bit like a function call (there is a function call involved, but we'll save those details for another time). For now, just understand it as "we made a new object and used some syntactic trickery to initialize it with data at the same time."

`ArrayObject` is essentially an object "wrapper" around the `array` data type, which provides certain required functionality. Our function `countAndIterate()` will only accept an object that has both `ArrayAccess` and `Countable` interfaces, which `ArrayObject` has, which makes `$obj` a valid value, so the call succeeds.

Disjunctive Normal Form Types

DNF types are a new feature in PHP 8.2; this rather intimidatingly named feature is simply a syntax that allows the mixing of union and intersection types. It's probably easiest to conceptualize DNF as an expression of a union type containing intersections, with the intersections enclosed in parentheses. Imagine we had three classes – named A, B, and C – and we wanted to declare that a type was allowed to be either the intersection A&B or A&C. The DNF would be `(A&B)|(A&C)`. We could take things further and add some base types, e.g., `(A&B)|(A&C)|array|null`. Just remember that all intersections (anything requiring an `&`) must be enclosed in parentheses.