```
echo sprintf('%s %s', 'hello', 'world') . PHP_EOL;
echo sprintf('%s %s %s', 'a', 'longer', 'string') . PHP_EOL;
```

```
Output:
hello world
a longer string
```

PHP provides a few useful built-in functions to help us handle variable numbers of arguments at run time: `func_num_args()`, `func_get_arg()`, and `func_get_args()`. Respectively, they will return a count of arguments used when the function is called, a specific argument, or an array of all arguments:

```
function testArgs(): void
{
    print "testArgs was called with " . func_num_args() . " arguments" .
    PHP_EOL;
    print "first argument value is " . func_get_arg(0) . PHP_EOL;
    print_r(func_get_args());
}

testArgs('I', 'hope', 'this', 'makes', 'sense');
```

```
Output:
testArgs was called with 5 arguments
first argument value is I
Array
(
    [0] => I
    [1] => hope
    [2] => this
    [3] => makes
    [4] => sense
)
```

We call `testArgs()` with five string arguments: `testArgs('I', 'hope', 'this', 'makes', 'sense')`. `func_num_args()` tells us we have five arguments and `func_get_arg(0)` returns the first (or zeroth, if you prefer) argument which is `'I'`; `func_get_args()` returns an array containing every argument.