Logical Expressions

We've now seen all of PHP's control structures, and to demonstrate them, some logical expressions were required. These expressions were necessarily simple to keep the examples clear. Typically, just simple comparison tests were used. If you've read Chapter 5, "Arrays," Chapter 7, "Numbers," and Chapter 8, "Strings," you'll be familiar with comparison operators. Let's just quickly summarize them again:

Comparison Operators

Table 4-3. *Comparison operators*

==	`true` if both operands are equal (types will be coerced)
===	`true` only if both operands are of the same type and equal
!=	`true` if both operands are not equal (types will be coerced)
!==	`true` if both operands are not equal or not the same type
<	`true` if the left-hand operand is less than the right-hand
>	`true` if the left-hand operand is greater than the right-hand
<=	`true` if the left-hand operand is less than or equal to the right-hand
>=	`true` if the left-hand operand is greater than or equal to the right-hand
<=>	Returns zero, less than zero, or greater than zero, depending on operand value

```
var_dump(1 == '1'); // true
var_dump(1 === '1'); // true
var_dump(1 != 1); // false
var_dump(1 !== '1'); // false
var_dump(1 <=> 0); // 1 - left-hand is greater
var_dump(1 <=> 1); // 0 - equal
var_dump(1 <=> 2); // -1 - left-hand is lesser
```