```
$arr1 = [
    'a' => 'Alice',
    'b' => 'bob',
];

$arr2 = ['Alice', 'Bob'];

extract($arr1);
extract($arr2, EXTR_PREFIX_ALL, 'student');

print "\$a: {$a}\n";
print "\$b: {$b}\n";
print "\$student_0: {$student_0}\n";
print "\$student_1: {$student_1}\n";

Output:
a: Alice
b: bob
$student_0: Alice
$student_1: Bob
```

`extract($arr1)` initializes two new variables using the keys of `$arr1` as the variable names: `$a` has the same value as `$arr1['a']`, and so on. For the indexed array `$arr2`, we specify a prefix for the new variable names and pass the flag `EXTR_PREFIX_ALL`. This tells `extract()` that we wish each new variable name to begin with the string `"student_"`, which has the happy effect of making our new names legal. Without `EXTR_PREFIX_ALL`, no variables would have been imported.

`extract()` has a return value: an integer value of the number of variables successfully imported and a variety of flags that can be passed as arguments to control its behavior. The default behavior is to overwrite any existing variables:

```
$name = 'Alice';
$arr = [
    'name' => 'Bob'
];
extract($arr); // $name will be overwritten
print "\$name: {$name}" . PHP_EOL;
```