Table 5-1. *`extract()` flag constants*

Flag	Effect
`EXTR_OVERWRITE`	Overwrite any existing vars (default)
`EXTR_SKIP`	Skip if var already exists
`EXTR_PREFIX_SAME`	Prefix vars on collision
`EXTR_PREFIX_ALL`	Prefix all vars
`EXTR_PREFIX_INVALID`	Prefix if var name would be invalid (e.g., numeric)
`EXTR_IF_EXISTS`	Only import var if existing
`EXTR_PREFIX_IF_EXISTS`	Prefix only if var already exists
`EXTR_REFS`	Create vars as refs to original array elements

In all cases except `EXTR_REFS`, only one flag is allowed, and if the flag would result in a prefixed variable being created, then the prefix argument must be given, we saw this earlier when we extracted from an indexed array – `extract($arr2, EXTR_PREFIX_ALL, 'student');`. `EXTR_REFS` is an interesting one because it can be combined with another flag and will result in the new variables being created as references to the original element; this is demonstrated below:

```
$arr = [
    'name' => 'Bob',
    'age' => 'Forty-seven',
    'favouriteToy' => 'Benelli M4 Tactical',
];

extract($arr, EXTR_REFS|EXTR_PREFIX_ALL, 'rusty');

$rustyName = 'Russell';
$rustyAge = 'Eleven';
$rustyFavouriteToy = 'Action Mans';

var_dump($arr);
```