Comparison Operators

PHP has various comparison operators, as we have seen in previous chapters. Valid array comparison operators are given in the table below.

Table 5-2. *Array comparison operators*

==	Equality: `true` if values equal (types coerced)
===	Identity: `true` only if values equal *and* types match
!=	Inequality: `true` if values not equal (types coerced)
!==	Non-identity: `true` if values not equal, or types don't match
<>	Inequality (alternate form)

These operators should already be familiar to you, if not then feel free to take a quick look at Chapter 4, "Logic and Control." The following example summarizes their use, output is given in the code comments in-line with each `var_dump()`:

```
$indexed1 = [0, 1, 2];
$indexed2 = [0, 1, 2];
$indexed3 = ['0', 1, '2'];
$indexed4 = ['0' => '0', 1 => 1, '2' => '2'];

$assoc1 = ['make' => 'VW', 'model' => 'Golf', 'variant'  =>  'GTI'];
$assoc2 = ['variant'  =>  'GTI', 'make' => 'VW', 'model' => 'Golf'];

var_dump($indexed1 == $indexed2); // true
var_dump($indexed1 == $indexed3); // true
var_dump($indexed1 == $indexed4); // true

var_dump($indexed1 === $indexed2); // true
var_dump($indexed1 === $indexed3); // false
var_dump($indexed1 === $indexed4); // false

var_dump($assoc1 == $assoc2); // true
var_dump($assoc1 === $assoc2); // false
```