## Find Key of Value

`in_array()` simply tells you if a value exists in array. If you need to know *where* the value is (or at least the first occurrence), then `array_search()` is the tool for the job:

```
$arr = ['Alice', 'Bob', 'Russell'];

$artists = [
    'Jimi Hendrix' => 'Stratocaster',
    'Eric Clapton' => 'Les Paul',
    'Dave Gilmour' => 'Stratocaster',
];

print "Bob is element no. " . array_search('Bob', $arr) . "\n";
print array_search('Stratocaster', $artists) . " played a Stratocaster\n";

Output:
Bob is element no. 1
Jimi Hendrix played a Stratocaster
```

`array_search($val, $array)` returns the key for the first instance of `$val` it finds or false if the value isn't found. There are two Stratocaster playing genius guitarists in `$artists` but Jimi is the first one found. Pop quiz: how would you fetch all of the Stratocaster players? `array_intersect($artists, ['Stratocaster']);` will do the job!

## Minimum and Maximum Values

PHP provides the functions `min()` and `max()`, which work in two ways: finding the largest and smallest values in an array (e.g., `min($array)`) or comparing two scalars (e.g., `max($val1, $val3)`). The results of calling this on an array of numbers should be obvious. For mixed data types, the standard comparison rules apply:

```
$arr = [1, 2, 3];

print "min val of \$arr: " . min($arr) . "\n";
print "max val of \$arr: " . max($arr) . "\n";

Output:
min val of $arr: 1
max val of $arr: 3
```