```
    [1] => stdClass Object
        (
            [model] => Fender Stratocaster
            [year] => 1962
        )

    [2] => stdClass Object
        (
            [model] => Ibanez Jem 777
            [year] => 1988
        )

)
```

Here we build three objects that all created from PHP's built-in `stdClass`, and add `year` (of manufacture) and `model` properties to them, to create three distinct objects. The three objects are stored in the `$guitArr` (ahem, sorry) array, and our task is to sort them by the year of manufacture.

The anonymous function given to `usort()` is called repeatedly to compare two objects and determines the order based on comparison of the `year` property of each object. The final, sorted array has a `'Fender Telecaster'` at the start (1958 was a good year for them), `'Fender Stratocaster'` in the middle (made in 1962, also a great year), and an `'Ibanez Jem 777'` at the end (being a relative youngster, still awesome instruments though).

`usort()` iterates the array and calls the anonymous function repeatedly to compare two objects. The anonymous function simply compares the `year` property of each object, using a spaceship operator `<=>`. This way `usort` can figure out if `$a->year` is less-than, equal-to, or greater-than `$b->year`. By comparing different pairs of elements against each other, the array is eventually sorted (using the *Quicksort* algorithm, if you are wondering). The resulting sorted array has `'Fender Telecaster'` at the start (1958 was a good year for them), `'Fender Stratocaster'` in the middle (made in 1962, also a great year), with `'Ibanez Jem 777'` at the end (wonderful things, thanks, Uncle Steve).