Perhaps you've been wondering up until now why the syntax for instantiating classes included a function-call-like set of parentheses? Well, that's the mechanism for passing data into the constructor method: it's an automatic call to the object's `__construct()` method once the object has been created by the `new` keyword. Now we can initialize our `QuoteBot` with the desired state (the array of quotes) as we create it:

```
$quoteBot2 = new QuoteBot([
    "Don't get uptight with me, man." . PHP_EOL,
    "I could take double anything you could." . PHP_EOL,
    "Very, very foolish words, man." . PHP_EOL,
]);
```

PHP 8 introduces a convenience feature called *constructor property promotion*. This allows us to use a shorthand syntax on the constructor declaration to automatically (automagically?) have class properties defined. Let's use that feature for the `$quoteStash` property:

```
class QuoteBot
{
    private int $numQuotes;

    public function __construct(private array $quoteStash)
    {
        $this->numQuotes = count($this->quoteStash) - 1; // used as
                                                            array index
    }

    // ... rest of class code
}
```

We've removed the explicit declaration `private array $quoteStash = [];`, and added a visibility keyword to the parameter of `__construct()`. Any variable in the constructor parameters that is given a visibility keyword is automatically set as a property (of the same name) on the class. In this example we are creating the `$this->quoteStash` array when the constructor is called (and an array is passed in). We can, of course, also promote `protected` and `public` properties this way.