The full list of PHP's magic methods and their calling contexts is as follows:

Table 6-1. *Magic methods*

Method	Context
`__construct()`	Object instantiation - `new SomeClass()`
`__destruct()`	Object destruction - `unset($obj)`
`__call()`	If inaccessible method is invoked - `$obj->inaccessible()`
`__callStatic()`	If inaccessible static method is invoked - `$obj::inaccessible()`
`__get()`	If inaccessible is read - `$obj->inaccessible`
`__set()`	If inaccessible is written - `$obj->inaccessible = 'val'`
`__isset()`	If `isset()` or `empty()` called with inaccessible property - `isset ($obj->inaccessible)`
`__unset()`	If `unset()` called with inaccessible property - `unset($obj->inaccessible)`
`__sleep()`	Execute before serialization - `serialize($obj)`
`__wakeup()`	Execute after serialization - `unserialize($obj)`
`__serialize()`	Return assoc. array representation - `serialize($obj)`
`__unserialize()`	Return value (usually object) from serialized - `unserialize($str)`
`__toString()`	Used as a string - `print $obj` etc.
`__invoke()`	Called as a function - `$obj()`
`static __set_state()`	When used with `var_export($obj)`
`__debugInfo()`	When used with `var_dump($obj)`
`__clone()`	When cloned - `$new = clone $obj`

All magic method names are prefixed with two underscore characters, and methods named in this way are reserved, so don't use __ to prefix your own method names.