Older versions of the Remi repository use a slightly different naming convention for the top-level PHP packages, such as `php74-php-7.4.*.remi.x86_64` so you might need to adjust your `grep` pattern accordingly. The pattern `php74` would return dozens of matching packages because PHP is a fairly modular language: most of it is implemented as extensions (or modules) which can be installed independently. Let's go ahead and install PHP versions 7.4 and 8.4 onto our system.

```
$ sudo dnf install -y php74-php-0:7.4.33-24.fc42.remi.x86_64
$ sudo dnf install -y php84-php-0:8.4.12-1.fc42.remi.x86_64
```

There's a slight difference from Debian here…

```
$ which php
which: no php ...
```

… although the packages end up on the system, there's still some legwork to do. The PHP binaries are accessible after installation, just under slightly different names:

```
$ ls -l /usr/bin | grep php
lrwxrwxrwx 1 root root  32 Aug  1 00:00 php74 -> /opt/remi/php74/root/
                                                 usr/bin/php
lrwxrwxrwx 1 root root  36 Aug  1 00:00 php74-cgi -> /opt/remi/php74/root/
                                                     usr/bin/php-cgi
lrwxrwxrwx 1 root root  38 Aug  1 00:00 php74-phar -> /opt/remi/php74/root/
                                                      usr/bin/phar.phar
lrwxrwxrwx 1 root root  32 Aug 29 00:00 php84 -> /opt/remi/php84/root/
                                                 usr/bin/php
lrwxrwxrwx 1 root root  36 Aug 29 00:00 php84-cgi -> /opt/remi/php84/root/
                                                     usr/bin/php-cgi
lrwxrwxrwx 1 root root  38 Aug 29 00:00 php84-phar -> /opt/remi/php84/root/
                                                      usr/bin/phar.phar

$ which php84
/usr/bin/php84
```