```
Loading MyApplication\SubNamespace\SomeOtherClass from /usr/src/myapp/
MyApplication/SubNamespace/SomeOtherClass.php
Loading MyApplication\SubNamespace\ThisClassOverHere from /usr/src/myapp/
MyApplication/SubNamespace/ThisClassOverHere.inc
```

Notice how `ThisClassOverHere` has been loaded by the first autoload function, which will search for files ending in `.inc`? Obviously, this is a contrived example (we could test for .inc and .php files in a single function) but serves to illustrate the principle. The popular Composer dependency manager uses multiple autoload functions internally to provide support not only for PSR-4 compliant projects but also for the older (now deprecated) PSR-0 standard and even support for loading classes that otherwise could not be autoloaded at all.

Object Utilities

We've covered a lot of material in this chapter, and hopefully you now have a thorough grounding in PHP's object model. Let's wrap things up with a look at the extra utility PHP provides beyond the object model itself. There are several built-in functions and other features in PHP to make working with objects and classes easier and code more concise.

Magic Constants

We've seen a useful magic constant already, `__NAMESPACE__`, it's called a magic constant because its value changes depending on where it is used. Here's all of the magic constants related to OOP.

Table 6-2. *Magic constants*

Constant	Value
`__CLASS__`	Class name including namespace
`__METHOD__`	Method name including class and namespace
`__NAMESPACE__`	Current namespace
`__TRAIT__`	Trait name including namespace