```
Output:
Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed
do eiusmod tempor incididunt ut labore et dolore magna aliqua.
```

The heredoc operator <<< is followed by an identifier symbol (which follows the same naming rules as variables and functions), which must then be immediately followed by a newline. By convention, heredoc identifiers are uppercase and contain only A–Z alphabet characters, but you are free to use digits (provided they are not the first character), underscores, and so on. Every character following the newline is then treated as string text until the identifier is repeated on a terminating line (and it must occur as the only text on that line), followed by a semicolon and then another newline.

PHP 7.3 or later allows the terminating identifier to be indented to the same minimum level as the text it contains (prior to that it had to begin on the first column of a newline), and indentation of the string output is relative to the indentation of the terminating identifier:

```
$heredoc = <<< TNG
    Captain's log, stardate 43930.7. The Enterprise has been in attendance
    at the biennial Trade Agreements Conference
        on Betazed. For the first time, the Ferengi are present...
  TNG;

print $heredoc . PHP_EOL;

Output:
  Captain's log, stardate 43930.7. The Enterprise has been in attendance at
  the biennial Trade Agreements Conference
      on Betazed. For the first time, the Ferengi are present...
```

If the terminating identifier is indented incorrectly, an error will be emitted:

```
$heredoc = <<< TNG
    Captain's log, supplemental. I have just been advised of a highly
    unusual project undertaken by Commander Data.
      TNG;

Output:
Parse error:  Invalid body indentation level (expecting an indentation
level of at least 6)
```