```
print_r(str_getcsv($species, separator: '|', escape: '\\'));
```

```
Output: (for both print_r() statements)
Array
(
    [0] => Dentrassis
    [1] => Dolphins
    [2] => G'Gugvuntt
    [3] => Vl'hurgs
    [4] => Golgafrinchans
)
```

CSV as a method of structured data interchange dates way back to the days of flared trousers, loud shirts, and IBM FORTRAN (the 1970s, in case you don't remember). As you can see from the example above, values are delimited by a comma by default but can be separated by any character (in the second case this is the pipe character; the ASCII horizontal tab character *0x09* is another common choice). This is quite a common method of structuring data, and it is by no means unusual to see it in use today. I would, however, advise that you take care when using `str_getcsv()` and exercise particular caution around what constitutes valid CSV data in your application. Let's take a look at more complex cases.

```
$csvRow1 = "Douglas Adams,"
    . "you may think it's a long way down the road to the chemist's, but
    that's just peanuts to space.";
$csvRow2 = "Iain M. Banks,"
    . '"I am not an animal brain, I am not even some attempt to produce an
    AI through software running on a computer"';

print_r(str_getcsv($csvRow1, escape: '\\'));
print_r(str_getcsv($csvRow2, escape: '\\'));
```

```
Output:
Array
(
    [0] => Douglas Adams
    [1] => you may think it's a long way down the road to the chemist's
    [2] =>  but that's just peanuts to space.
)
```