This Nginx configuration syntax defines a server that listens to traffic on TCP 80 from any external address and the server's filesystem root is `/var/www/html` (remember our volume mount in `docker-compose.yaml`). The default index file is `index.php` (i.e., a request to http://localhost/ will be mapped to `/var/www/html/index.php`), and any request URIs that end in `.php` will be proxied to TCP 9000 on the host `php-fpm`. Notice that this host has the same name as one of our services in `docker-composer.yaml`: when `dockerd` adds the containers to the shared network their names are resolvable to IP address (all handled magically for you by `dockerd`). The `nginx` container is able to resolve the hostname `php-fpm` to that container's IP address. TCP 9000 is the default port that the `php:8.4-fpm` container is configured to listen to, so there's no need for any extra config.

The only thing we need now is `index.php`, so let's create that next.

```
<?php

echo "<pre>Hello from php-fpm!</pre>";
echo "<pre>We are running under " . PHP_SAPI . " SAPI</pre>";
```

You should now have the following files in whichever directory you are working in:

```
$ tree --charset=asci
.
|-- Dockerfile
|-- default.conf
|-- docker-compose.yaml
`-- index.php

1 directory, 4 files
```

All that's left now is to tell Docker to bring up the containers:

```
$ docker compose up
[+] Running 2/2
 ✓ Container nginx-php-fpm-nginx-1    Created
 ✓ Container nginx-php-fpm-php-fpm-1  Created
Attaching to nginx-php-fpm-nginx-1, nginx-php-fpm-php-fpm-1
 ...
nginx-php-fpm-nginx-1  | 2023/10/14 17:37:52 [notice] 1#1: start
worker process
```