0049; tr Not_Before_Dot;. In plain language, this means "U+0049 I maps to U+0131 ı when lower, U+0049 when title, U+0049 when upper, for the 'tr' region, and only where the source character is *not immediately before a dot*" (we'll come back to this last clause shortly; it's important).

Likewise, the special rule for uppercasing i to İ is 0069; 0069; 0130; 0130; tr;: "U+0069 i maps to U+0069 for lower. U+0130 İ for upper and title, for the 'tr' region." The eagle-eyed will have spotted something here: title case (as a character mapping, rather than a conversion pattern applied at word boundaries). The fun fact is that Unicode has three cases: upper, lower, and title. For most practical purposes, uppercase and title case character mappings are identical, and the distinction exists purely for a few edge cases involving combined characters. We'll limit the rest of this section on case conversion to upper and lower.

Continuing with our example code, after setting the locale to 'tr_TR.UTF-8', we then go on to call mb_convert_case() with two conversions that will reveal the underlying rules – i to upper and I to lower. Clearly the special rules are not enforced: i uppercased to I (U+0049) and I lowercased to i (U+0069), which are the normal Unicode rules for case mapping, despite explicitly setting our language locale to a UTF-8 variant of 'tr'. But the complications of case mapping are not limited to regional alphabets; there are some quirky rules that are restricted to character sets that are not related to the ASCII Latin range. Let's have a quick look at Greek, which has two variant lowercase letters for Sigma Σ…

```
/*
 * Special
 * 03A3; 03C2; 03A3; 03A3; Final_Sigma; # GREEK CAPITAL LETTER SIGMA
 * Σ > ς (03C2 if final letter)
 *
 * Normal
 * 03A3;GREEK CAPITAL LETTER SIGMA;Lu;0;L;;;;;N;;;;03C3;
 * Σ > σ (03C3)
 */

$finalSigmaTest = "FINAL\u{03A3} \u{03A3}NON-FINAL";
print $finalSigmaTest . PHP_EOL;
print mb_convert_case($finalSigmaTest, MB_CASE_LOWER);
```