Quite interesting, we've got an ASCII lowercase i *0x69*, followed by a (UTF-8) combining dot *0xCC 0x87*. Looks weird in code, might possibly look weird rendered too (hopefully the font chosen by your OS or web browser has the dots of the two combined glyphs perfectly aligned). In case you might be wondering, the `UnicodeData.txt` case conversion rules are being followed here: `"\u{49}\u{307}"` maps to `\u{69}\u{307}` (and vice versa), and `"\u{130}"` has a one-way mapping to `\u{69}\u{307}`. The 'tr' region-specific special rule for lowercasing `"\u{49}\u{307}"` would result in just single *0x69* byte.

This equivalence of single- and multi-codepoint characters raises another question: how can we evaluate that equivalence programmatically? Case-mapping is good for changing text and respecting the rules and expectations of a human audience, but…

```
print bin2hex($singleCodepointChar) . PHP_EOL;
print bin2hex($multiCodepointChar);
```

```
Output:
c4b0
49cc87
```

… clearly a dumb machine will look at the byte values and decide they're not the same thing. If only there was a special case conversion that was able to put the needs of machines over the needs of humans. Well, we could do what we just did above and lowercase the two versions of İ, but that would actually fail if `mb_convert_case()` implemented the 'tr' special regional rules. The conversion types of `MB_CASE_UPPER` and `MB_CASE_LOWER` are not intended to produce canonical results across all possible locales, character sets, and other complicating factors. There are also many other special rules; uppercase conversion might work for some, lowercase might work for others, and neither will work for all. The good news is that Unicode does make provision for precisely this scenario, with a related rule set called *case folding*, which is intended to produce consistent results that are independent of regional or other issues.

```
$singleCodepointChar = "\u{130}";
$multiCodepointChar = "\u{49}\u{307}";

var_dump(
    mb_convert_case($singleCodepointChar, MB_CASE_FOLD) ===
    mb_convert_case($multiCodepointChar, MB_CASE_FOLD)
);
```