```
Output:
c581756b61737a
```

... or we can be more explicit about the source and target encoding types:

```
mb_internal_encoding("UTF-8");
print bin2hex(mb_convert_encoding(
    "\x01\x41\x00\x75\x00\x6b\x00\x61\x00\x73\x00\x7a",
    to_encoding: 'UTF-8',
    from_encoding: 'UTF-16BE'
));
```

```
Output:
c581756b61737a
```

`mb_convert_encoding()` will also accept an array of strings and will convert every element's encoding in the same way as demonstrated above.

mb_convert_variables()

If you find yourself in the unenviable position of needing to convert many strings in one call, `mb_convert_variables()` will take a variety of inputs and convert them for you.

```
$determinist = "\x00\x44\x00\x65\x00\x74\x00\x65\x00\x72\x00\x6d"
    . "\x00\x69\x00\x6e\x00\x69\x00\x73\x00\x74";
$revisionist = "\x00\x52\x00\x65\x00\x76\x00\x69\x00\x73\x00\x69"
    . "\x00\x6f\x00\x6e\x00\x69\x00\x73\x00\x74";

mb_convert_variables(
    'UTF-8',
    'UTF-16BE',
    $determinist,
    $revisionist
);

print bin2hex($determinist) . PHP_EOL;
print bin2hex($revisionist);
```

```
Output:
44657465726d696e697374
5265766973696f6e697374
```