```
    $text
);
```

```
Output:
Çağari
ÇAĞARI
```

`mb_ereg_search_init()`, `mb_ereg_search()` et. al.

Now we come to a group of related functions, which are the core of the `mbstring` regex functions. A sample string is initialized with a pattern like so:

```
$text = <<<EOS
Demelza: V\u{1EB1}n th\u{1EAF}n, H\u{1EE7} ti\u{1EBF}u
Paul: C\u{01A1}m chi\u{00EA}n D\u{01B0}\u{01A1}ng Ch\u{00E2}u
EOS;
print $text . PHP_EOL;

mb_ereg_search_init($text);
```

```
Output:
Demelza: Vằn thắn
Paul: Cơm chiên Dương Châu
```

As we can see, Paul and Demelza are off to eat some delicious Vietnamese food. We can break the complete string into whatever pieces we like using different patterns at different points. `mb_ereg_search($pattern)` will apply a regex to the string that was initialized with `mb_ereg_search_init()`, and the results can be obtained by calling `mb_ereg_search_getregs()`:

```
// $text = ...; mb_ereg_search_init($text);
mb_ereg_search('^\w+:\s');
print_r(mb_ereg_search_getregs());
```

```
Output:
Array
(
    [0] => Demelza:
)
```