At this point, the PCRE engine has consumed part of the sample matching `^\w+:\s` which is the sub-string `'Demelza: '`. The next call we make will start at `'Vằn thắn...'`. We can then perform another search with a different pattern. We can also perform the search and obtain the results in a single call with `mb_ereg_search_regs()`, so let's do that. The following code executes immediately after the previous example (it is now the second `mb_ereg_search_regs()` in the chain):

```
print_r(mb_ereg_search_regs('[^,\r\n]+'));
```

```
Output:
Array
(
    [0] => Vằn thắn
)
```

Now we're asking for a match on any character that isn't a comma, newline, or carriage return by using the negated character class `[^,\r\n]+`. We're using both `\r` and `\n` because different operating systems use slightly different line endings. Every call to `mb_ereg_search()` and `mb_ereg_search_regs()` will consume any matching parts of the sample string, so the next thing we'll do is gobble up the newlines. Then we can grab some more text that we care about, as the third `mb_ereg_search()` call:

```
mb_ereg_search('[\r\n]+');

print_r(mb_ereg_search_regs('\w+:\s'));
print_r(mb_ereg_search_regs('[^,\r\n]+'));
```

```
Output:
Array
(
    [0] => Paul:
)
Array
(
    [0] => Cơm chiên Dương Châu
)
```