Literal values are strings, numbers, and other raw values that do not require evaluation in order to have a value.

Now that is a lot to take in, so let's summarize with some code examples:

```
declare(strict_types=1); // Header statement

namespace Foo; // Header statement

class ClassDeclarationsAreStatements // General statement
{
}

function functionDeclarationsAreAlsoStatements () // General statement
{
}
```

The example above shows header statements (`declare()` and `namespace`) and the "special" general statements declaring a class and a function. Classes and functions are covered in detail in Chapter 3, "Functions," and Chapter 6, "Object Fundamentals," and the execution directive `declare(string_types=1)` in the next chapter. These are all special statements, and notice that the class and function declarations don't require semicolon terminators.

With the special cases out of the way, here are some examples of general statements that are composed of lower-order terms, such as expressions and operations. Remember that all symbols, operations, and expressions delimited by semicolons form the statement. The simplest possible statement in PHP, therefore, is a single literal value:

```
// A single literal is still a valid statement...
1;

// An operation containing literal values, this is also an expression that
evaluates to 2
1 + 1;

// We can assign an operation to a symbol.
$number = 1 + 1;
```

Above are three statements. The first is a single literal value, the second is an operation composed of a single operator and two literal operands, and the third is an assignment expression that takes the value of a sub-expression (which is a simple