```
  php-fpm:
    image: php:8.4-fpm
    networks:
      - internal
    volumes:
      - ./:/var/www/html
networks:
  internal:
    driver: bridge
```

The Dockerfile that this depends on is as follows:

```
FROM nginx:1.25
ADD default.conf /etc/nginx/conf.d
```

The only thing left to do is run `docker compose`, which should leave us with a containerized `nginx` server. This `nginx` instance is configured to serve a default `index.php` script if the URL doesn't specify a particular resource. Stop any other running containers, such as the PHP `cli-server` from earlier, using `docker ps` and `docker container stop`, then get building:

```
$ docker compose up
...
 ✓ Container nginx-php-fpm-1  Created       0.1s
 ✓ Container nginx-nginx-1    Created       0.1s
Attaching to nginx-nginx-1, nginx-php-fpm-1
...
nginx-php-fpm-1  | [28-Aug-2025 15:56:51] NOTICE: fpm is running, pid 1
nginx-php-fpm-1  | [28-Aug-2025 15:56:51] NOTICE: ready to handle
connections
```

The last two lines in the log output ("fpm is running" and "ready to handle connections") let us know that the `nginx` container is now running in the foreground and logging to STDOUT/STDERR. Make sure the following code is placed in `index.php`, which must reside in the same directory where you ran `docker compose up`:

```
$routes = [
    'new.article' => [
        'method' => 'POST',
```