```
> Content-Type: multipart/form-data; boundary=------NqepV8M1YXB3iLRd1yjoCOp
* upload completely sent off: 612379 bytes
< HTTP/1.1 200 OK
...
array(1) {
  ["file"]=>
  array(6) {
    ["name"]=>
    string(10) "random.jpg"
    ["full_path"]=>
    string(10) "random.jpg"
    ["type"]=>
    string(10) "image/jpeg"
    ["tmp_name"]=>
    string(27) "/tmp/phptlpptkkrp5rf0azkKKY"
    ["error"]=>
    int(0)
    ["size"]=>
    int(612179)
  }
}
```

Note the `Content-Type:` header is set to `multipart/form-data` with an additional component: `boundary=------------------qepV8M1YXB3iLRd1yjoCOp`. This is the boundary string separating the parts of the request data, but you won't need to worry about that; by the time PHP passes control to your code, it will have processed the request body into POST data structure(s) and file data. This is controlled by `Content-Disposition:` and `Content-Type:` sub-headers in the multipart body, the raw request data from the above would look like this:

```
POST /index.php HTTP/1.1
Content-Type: multipart/form-data; boundary=--------------------
qepV8M1YXB3iLRd1yjoCOp
--------------------qepV8M1YXB3iLRd1yjoCOp
Content-Disposition: form-data; name="file"; filename="random.jpg"
Content-Type: image/jpeg

<BINARY_DATA>
```