You can see that we did not set our status code to 403, and we get an error. In this case the error message – "`Warning: http_response_code(): Cannot set response code – headers already sent...`" – is appended to the response body as formatted HTML, which is what the official `php:8.4-cli` docker image is configured to do. Depending on your setup, you might need to take a look in the error logs. This is logical; the status code and headers were already sent to the client when we started to create output from our program. There's no way for us to change them and not break the HTTP protocol. There is a way round this, which we will be examining at the end of this section.

Response Headers

Hopefully by now you'll be quite comfortable with HTTP headers and what they do. Some common and important HTTP/1.1 headers typically seen in responses are:

Table 11-4. *Common response headers*

`Cache-Control:`	Fine control of browser caching
`Connection`	Keep network connection after current response, deprecated in HTTP/2
`Content-Type:`	IANA media type, possible `charset` param indicates encoding
`ETag:`	Version control of resources, for browser cache and bandwidth efficiency
`Expires:`	Controls expiry of browser cached resources
`Last-Modified:`	Controls browser caching, crawler frequency
`Location:`	Controls client redirection in `3xx` responses
`Set-Cookie:`	Sets a cookie key/value pair

To set a header in PHP, simply use the built-in `header()` function. You can also view the current response headers (before or after they are sent) with the `apache_response_headers()`, which (despite the name) is available in a variety of server SAPIs, including `cli-server` and `php-fpm`. Remember the problematic `X-Powered-By:` header from earlier? Let's get rid of that:

```
$headers = apache_response_headers();
header("X-Powered-By: none/of-your-business");
var_dump($headers);
print "Thanks for visiting!";
```